



# *CANDU Safety* *#8 - Containment*

Dr. V.G. Snell  
Director  
Safety & Licensing



## *What's Special About CANDU Containment?*

- λ not much
- λ containment type is not tied to the CANDU design:
  - single unit pressure suppression (CANDU 6)
  - multi-unit vacuum pressure suppression (Ontario Hydro)
  - double containment with suppression pool (recent Indian HWRs)
  - single-unit dry (CANDU 9)



# *Single Unit Pressure Suppression (CANDU 6)*






## *Fundamental Requirements*

- λ design pressure set above pressure reached in large LOCA
- λ leak rate at design pressure set to ensure the dose to the public in an accident is less than the regulatory limit
- λ note that the dose is *calculated* from:
  - release to containment using physically-based models of reactor physics, fuel, reactor thermohydraulics, etc.
  - containment pressure transient using physically-based models of containment thermohydraulics
  - atmospheric dispersion models



# Single-Unit Pressure Suppression





## *Design Summary - CANDU 6*


- λ prestressed, post-tensioned concrete structure
  - keeps the building in compression
- λ relatively *large*
  - 41 metres ID × 44 metres high; 48,000 m<sup>3</sup> net volume
  - diameter required for fuelling machines
  - large volume per unit energy allows lower design pressure (124 kPa (g))
- λ wall thickness: 1.1 metres
- λ walls lined with epoxy for leak-tightness
- λ design leakrate: 0.5% / day at design pressure





# Dousing

- λ powerful pressure suppression, *not* like LWR sprays
- λ in elevated tank around building dome
- λ capacity 1560 m<sup>3</sup>, flowrate 4500 kg/sec for 4 out of 6 headers





## *Dousing Operation*


- λ 6 spray headers, each with 2 valves in series (to avoid inadvertent douse, which is costly)
- λ dousing turns on when building pressure reaches 14 kPa (g) and off if it falls to 7 kPa (g)
  - always on for large LOCA until dousing water is all used
  - cycles on & off for small LOCA
- λ dousing connections above bottom of tank so 500 m<sup>3</sup> of water is reserved for medium-pressure ECC
- λ assists in fission product washout
- λ no effect in long-term containment pressure control





## Long-Term Cooling

- λ 16 local air coolers
- λ condensation on structures and equipment
- λ for LOCA, emergency core cooling system heat exchangers





## ***Ventilation***

- λ in operation, most of the containment building is accessible, unlike most LWRs**
- λ ventilation is needed for working conditions and to control and condense heavy water vapour**
- λ on a containment isolation signal (high pressure or high radiation), redundant valves in each ventilation line to the atmosphere are closed - but *not* major process lines**
- λ unavailability of ventilation valve closure must be  $< 10^{-3}$  as with other safety systems**
- λ tested during operation to show the unavailability target is not exceeded**



## *Hydrogen Control*

- λ hydrogen can build up:
  - in the short term, from clad oxidation, in a severe accident such as a LOCA + Loss of Emergency Core Cooling
  - in the long term, after a LOCA, due to radiolysis
- λ natural circulation in containment and the size of the building reduces the hydrogen concentration for LOCA + LOECC
- λ forced flow from Local Air Coolers mixes hydrogen
- λ supplemented by 44 igniters to ignite local concentrations
- λ for “worst” LOCA + LOECC, maximum room hydrogen concentration is 7%; building average is 3.5%



## *Acceptance Criteria*

- $\lambda$  peak pressures must be less than design pressure for:
  1. LOCA
  2. LOCA with loss of emergency core cooling
  3. LOCA with loss of all dousing
- $\lambda$  there must be no structural failure which could damage the reactor systems for:
  4. steam or feedwater line break
  5. steam or feedwater line break with loss of all dousing
- $\lambda$  there must be no damage to the containment structure for items 1 to 4



## *Discussion of Design Pressure*

- λ containment pressure must be less than design for accidents which can release fission products
- λ this includes some *severe accidents* such as LOCA + LOECC
- λ containment leakage is not as important for accidents which do not release much radioactivity (and steam line breaks cause a power reduction, not an increase)
- λ the structural integrity of the building must be maintained even for some multiple failures




## *Overpressure Behaviour*

- λ in severe accidents which increase pressure far beyond design pressure, failure mode is “graceful”
  - increasing leakage through cracks
  - no massive failure
- λ AECB tests on scaled model CANDU 6 containment
  - through-wall cracks at 2.7 times design pressure, negligible leakage
  - failure at 4.3 times design pressure *if* pressure could be maintained
  - leakage rate increases rapidly and prevents failure



## Multi-Unit Vacuum Containment

- λ each reactor containment is connected by a large duct to a common vacuum building
- λ water sprays in vacuum building condense steam
- λ containment stays subatmospheric for days after an accident so the leakage is inward
- λ very powerful and allowed siting of CANDUs near major city (Toronto)



Pickering 8-Unit CANDU, near Toronto





# *Single Unit Dry Containment*

- λ CANDU 9
- λ dousing has been removed
- λ higher containment design pressure
- λ steel-lined for increased leak-tightness

