NUCLEAR REACTOR PROCESS SYSTEMS:

THERMAL HYDRAULIC ANAYSIS

prepared by: Wm. J. Garland, Professor
Department of Engineering Physics
McMaster University
Hamilton, Ontario
Canada
February 1998

for the Thailand Initiative

TABLE OF CONTENTS:

FORWARD v

GLOSSARY OF ABREVIATIONS AND ACRONYMS vii

Chapter 1 Course Overview 1-1
1.1 Introduction 1-1
1.2 Learning Outcomes 1-2
1.3 The Course Layout 1-3

Chapter 2 Basic Equations for Thermalhydraulic Systems Analysis 2-1
2.1 Introduction 2-1
2.2 Conservation 2-4
2.3 Conservation of Mass 2-6
2.4 Conservation of Momentum 2-8
2.5 Conservation of Energy 2-10
2.6 The Equation of State 2-15
2.7 Emperical Correlations 2-16
2.8 Solution Overview 2-16
2.9 Exercises 2-18

Chapter 3 Nodalization 3-1
3.1 Introduction 3-1
3.2 The Noble-Link Concept 3-2
3.3 Nodal Diffusion 3-3
3.4 Examples 3-4
3.5 Matrix Notation 3-5
3.6 Exercises 3-7

Chapter 4 Equation of State 4-1
4.1 Introduction 4-1
4.2 Thermodynamic Properties 4-2
4.3 The Iterative Method 4-3
4.4 The Rate Method 4-5
4.5 H_2O Property Fits 4-9
4.6 Exercises 4-11

Chapter 5 The Rate Form of the Equation of State 5-1
5.1 Introduction 5-1
5.2 The Rate Form 5-2
5.3 Numerical Investigations: a Simple Case 5-3
5.4 Numerical Investigations: a Practical Case 5-8
5.5 Discussion And Conclusion 5-11
5.6 Exercises 5-12

Chapter 6 Thermalhydraulic Network Simulations 6-1
6.1 Introduction 6-1
6.2 Porsching's Method 6-2
6.3 Dervation of FIBS 6-2
6.4 Special Cases 6-8
6.5 Programming Notes 6-9
6.6 Conclusion 6-10
6.7 Exercises 6-11

Chapter 7 Emperical Correlations 7-1
7.1 Introduction 7-1
7.2 Emperical Correlations 7-1
7.3 Two Phase Flow Void Correlations 7-2
7.4 Friction 7-3
7.5 Heat Transfer Coefficients 7-4
7.6 Thermodynamic Properties 7-4
7.7 Flow Regime Maps 7-5
7.8 Special Component Data 7-5
7.9 Exercises 7-8

Chapter 8 On Design Tools 8-1
8.1 Introduction 8-1
8.2 The Model's Tenuous Link to Reality 8-1
8.3 Documentation, Verification and Validation 8-2
8.4 Design Tools 8-2
8.5 Notes on Steam Generator Modelling 8-10

References R-1

LISTS:

Table 4.1 Summary of the F functions for the rate form of the equation of state 4-12
Table 4.2 Summary of the G functions for the rate form of the equation of state 4-13
Table 5.1 Figure of Merit Comparisons of the Normal and Rate Forms of the Equation of State for Various Convergence Criteria (Simple Case). 5-13
Figure 1.1 Concept map for the course 1-4
Figure 1.2 The cognitive domain 1-5
Figure 2.1 Derivation path 2-19
Figure 2.2 The four cornerstone single phase equations and the flow of information between them 2-20
Figure 2.3 The four cornerstone equations for the full two-fluid model 2-21
Figure 2.4 The four cornerstone equations for the two fluid model with equal pressure of the two phases 2-21
Figure 2.5 Simple pool-type research reactor 2-22
Figure 3.1 A general and connecting links 3-8
Figure 3.2 Two connected nodes 3-8
Figure 3.3 Node-link setup for a simple pipe 3-9
Figure 3.4 Node-link setup for an area change in a pipe 3-10
Figure 3.5 Illustration of convection and diffusion 3-10

Figure 3.6 Transmission of a step change using the plug flow model and a feeder model with skewing due to differences in transit times 3-11
Figure 3.7 Transmission of a step change using the Pluf Flow model and the Mixing Tank model (1 to 50 tanks) 3-11
Figure 3.8 Simple Tee junction 3-12
Figure 3.9 Simple Y junction 3-12
Figure 3.10 Sample node-link connections for a header 3-12
Figure 3.11 Node-link diagram: 1/4 circuit Darlington GS 3-13
Figure 3.12 Node-link diagram: Full circuit Darlington GS 3-14
Figure 3.13 4 node – 5 link diagram 3-15
Figure 4.1 P-v-T surface for water 4-13
Figure 4.2 Numerical search for P given $\sqcup$ and h for a two-phase mixture 4-13
Figure 4.3 Error correction scheme for pressure in two-phase 4-14
Figure 4.4 Density vs. pressure at various temperatures in subcooled water 4-14
Figure 4.5 Basis for curve fitting in the subcooled region 4-15
Figure 5.1 Simple 2-node, 1 link system 5-13
Figure 5.2 Program flow diagram for the normal method 5-14
Figure 5.3 Program flow diagram for the rate method 5-15
Figure 5.4 Number of iterations per pressure routine call for the normal method with a time step of 0.01 seconds and a pressure error tolerance of 0.001 of full scale (10 mPa) 5-16
Figure 5.5 Integrated flow error for the rate method and the normal method for various fixed time steps, convergence tolerances and adjustment factors 5-16
Figure 5.6 Schematic of control volumnes in the pressurizer 5-17
Figure 5.7 Flow vs. time for the implicit forms of the normal and rate method 5-17
Figure 5.8 Pressurizer's pressure transient for the normal method with error tolerance of 0.2% 5-18
Figure 5.9 Pressurizer's pressure transient for the rate method 5-18
Figure 5.10 Averaged number of iterations per pressure routine call for the normal method in simulating pressurizer problem 5-19
Figure 6.1 The simple 4 node – 5 link example 6-12
Figure 6.2 The four cornerstone equations for thermalhydraulic system simulation and the flow of information between them 6-12
Figure 7.1 Void fraction versus quality for mixtures of saturated liquid and vapour water 7-9
Figure 7.2 Π versus x and $\partial\Pi / \partial x$ 7-10
Figure 7.3 Flow regimes in horizontal pipes 7-11
Figure 7.4 Typical power distributions 7-12
Figure 7.5 Complete pump characteristics, double-suction pump, speed = 1800 rpm 7-13
Figure 7.6 Head characteristics for a typical CANDU pump 7-14
Figure 7.7 Torque characteristics for a typical CANDU pump 7-15
Figure 7.8 Choked flow characteristics for a valve 7-16
Figure 7.9 Control valve characteristics 7-16
Figure 7.10 Critical heat flux 7-17

Figure 7.11 Possible thermalhydraulic regimes in a coolant channel..... 7-18
Figure 7.12 Power and quality versus length along a fuel channel..... 7-19
Figure 7.13 Power versus quality..... 7-19
Figure 7.14 Critical Power Ratio determination..... 7-19